

PROCESSOR

600 MHz, Arm Cortex-A9 32-bit RISC, 1500 MIPS

MEMORY

384 MB (256 MB Flash, 128 MB SDRAM)

DISPLAY

2.8" QVGA, color LCD

OPERATING SYSTEM

V/OS (Linux-based)

CONNECTIVITY

Dial-up, Ethernet

PRINTER

30 lps, 40 mm paper roll

CARD READERS

Triple track MSR: ISO 7810, 7811, 7813; smart card reader: EMVCo-approved

CONTACTLESS

ISO 14443 Types A and B, ISO 18092capable, EMVCo L1 certification, MIFARE, supports major NFC/CTLS schemes

PERIPHERAL PORTS

2 USB connectors: 1 host, 1 host/client; 1 RS-232-powered

AUDIO

Buzzer

SECURITY

PCI PTS 5.X-approved

POWER SUPPLY

convenience and ease of use with advanced features designed to more

fully engage your customers at the point of sale.

AC input 100-240 VAC, 50/60 Hz; DC output 8 V 2.25 A

ENVIRONMENTAL

Operating temperature: 0° to 50° C (32° to 122° F); storage temperature: -20° to 60° C (-4° to 140° F); relative humidity: 5% to 90%, non-condensing

PHYSICAL

183 mm L × 80 mm W × 55 mm H; 295 g

OTHER STANDARD FEATURES

2 SAM slots, backlit keypad